

P. O. Box 1220, Nash, TX 75569-1220 Phone 800-527-8482 or 903-832-2581 Fax 800-874-9524 or 903-838-6260 www.jcmindustries.com

Typical Specification

JCM 168 Fabricated Lug Lightweight Stainless Steel Clamp

Full circumferential single band repair clamps shall have a minimum material standard of 304 stainless steel band, bolt assembly and hardware. Fabricated lug shall have permanently attached mutually supporting fingers and strong stainless steel lifter bar plate. The gasket shall be gridded with tapered lap joint ends and a 304 stainless steel bridge plate molded flush into the gasket. Gaskets in sizes 3" and larger shall be 1/4" thick. Clamps shall be JCM 168 Fabricated Lug All Stainless Sewer Steel Clamp or approved equal.

JCM 100 Series Clamps are ANSI/NSF Standard 61 and Standard 61 Annex G Certified. JCM 100 Series Universal Clamp Couplings meet or exceed ANSI/AWWA C230 Standard for Stainless –Steel Full-Encirclement Repair and Service Connection Clamps as applicable.



JCM 168 Fabricated Lug All Stainless Steel Sewer Clamp Coupling – 7" width

This typical specification, provided by JCM Industries, is a proposed guideline for use by specifying agencies to ensure significant design and material features of this product are included within the agencies' individual specifications.





P. O. Box 1220, Nash, TX 75569-1220 Phone 800-527-8482 or 903-832-2581 Fax 800-874-9524 or 903-838-6260 www.jcmindustries.com

Material Specification

JCM 168 Fabricated Lug Lightweight Stainless Steel Clamp

Bolt Assembly: 18-8 Type 304 Stainless Steel

Band: 18-8 Type 304 Stainless Steel

Bolts and Nuts: 18-8 Type 304 Stainless Steel

Gasket: Virgin Styrene-Butadiene Rubber (SBR) - Compounded for use with

water, salt solutions, mild acids and bases. Per ASTM D-2000 M4AA 607. Standard temperature range from -40° to 150° F (-40° to 65° C) constant, maximum intermittent 180° F (82° C). For applications on high temperatures or chemical pipelines, contact JCM Industries

Technical Services.

JCM 100 Series Clamps are ANSI/NSF Standard 61 and Standard 61 Annex G Certified. For ranges and widths, see JCM Industries General Product Directory Catalog. Information based on data available at the date printed below and subject to change without notice. Contact JCM Industries for amendments or changes.

