

CopperStopper™ and SteelStopper™

QT Style Line Stop Saddles for Copper Tubing & Steel/PVC Pipe

(Available by special order for Cast Iron, Ductile Iron and C900 Pipe Sizes)



Comes with Brass Completion Plug and Standard MI Cap

Specifications:

- Panel: Type 304 (18-8) Stainless steel per ASTM A240
- Gasket: Nitrile (Buna-N, NBR) Chek-O-Seal with multi o-ring sealing ribs from 100% new rubber to ensure performance under varying pressures with superior storage characteristics. Suitable for oils, acids, alkalines, most Hydrocarbon Fluids (aliphatic), portable water, and many other chemicals within temperature range of -40° F - $+180^{\circ}$ F.
- Lugs: Type 304 (18-8) Stainless steel per ASTM A240
- Bolts and Nuts: Type 304 (18-8) Stainless steel per ASTM A193 & A194. Note: Hex nuts are furnished with fusion bonded coating to prevent seizing and galling.
- Outlet: Schedule 80 Type 304/304L Stainless Steel seamless, machined
- All outlets are "Male Threaded NPT" outside
- Inlets threaded
- Brass Plug: half-hard, SAE, CA-360 per ASTM B-16
- Cap: Standard MI type
- Working Pressure: Maximum 150 PSI.

Distributed By:

PipeMan Products, Inc.

Toll Free: 1-877-PIPEMAN

(1-877-747-63626)

1647 Willow Pass Rd., #240, Concord, CA 94520

